



AXMINSTER 80 %Lana 20% Poliammide



Product

7x7 // 7x8 // 7x9 // 7x10 (product range)

Specification (in according to)

EN 1307 - EN 14159

Construction	Axminster carpet - cut pile
Pile Composition	80% Lana 20% Poliammide
Backing	PP/CO/PES
Stitches	± 76180 // 86940 // 97710 // 108750 n/m ²
Pile Height	± 7.1 mm
Total Height	± 10.2 mm
Total Yarn Weight	± 1050 // 1200 // 1350 // 1480 g/m ²
Yarn Count	Tex 330x2
Pitch	7
Rows	7 // 8 // 9 // 10
Total Weight (carpet finished)	± 2050 // 2160 // 2310 // 2450 g/m ²
Roll Width	400 cm
Insulation Impact Noise ΔLw	32 dB
Use Intensity Classification - Commercial	Class 33: Heavy
Reaction to Fire	Surface materials and floor coverings with low flame-spread characteristics: c) floor coverings - Item MED/3.18c
Electrical Behaviour – Body Voltage/Walking Test	≤ 2 kV
Luxury Class	Class LC3 // LC4 // LC5 // LC5
Stairs Suitability	A: Intensive use (commercial)
VOC	Pass

NOTES

RADICI MARINE reserves the right to update this sales sheet without giving prior notice.

Caption: // product range-nominal value

Reaction to Fire: testing standards IMO Res.MSC.307 (88) - (2010 FTP Code) Annex 1 Part 2-5

VOC= full details on regulations and protocols satisfied on demand

CONTACTS

www.radicimarine.it
 info@radicimarine.it
 +39 035 0950 231

RADICI PIETRO INDUSTRIES & BRANDS S.p.A. Via Cav. Radici, 19 - 24026 Cazzano Sant'Andrea (BG), Italy